

FDM Machine/Material Reference

Printer				
Printer	Build Envelope (XYZ)	Cartridge Or Canister Volume	External Dim. (WxDxH)	Layer Thickness (Z-Height)
Stratasys F120™	25.4 x 25.4 x 25.4 cm (10 x 10 x 10 in)	200 cu in	88.9 x 87.0 x 72.1 cm (35 x 35 x 29 in)	0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in)
Stratasys F170™	25.4 x 25.4 x 25.4 cm (10 x 10 x 10 in)	60 or 90 cu in	162.6 x 86.4 x 71.1 cm (64 x 34 x 28 in)	0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in)
Stratasys F270™	30.5 x 25.4 x 30.5 cm (12 x 10 x 12 in)	60 or 90 cu in	162.6 x 86.4 x 71.1 cm (64 x 34 x 28 in)	0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in), 0.127 mm (0.005 in)
Stratasys F370™	35.6 x 25.4 x 36.6 cm (14 x 10 x 14 in)	60 or 90 cu in	162.6 x 86.4 x 71.1 cm (64 x 34 x 28 in)	0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in), 0.127 mm (0.005 in)
Fortus 380mc™	35.6 x 30.5 x 30.5 cm (14 x 12 x 12 in)	92 cu in or 184 cu in	127 x 90.17 x 198.4 cm (50 x 35.5 x 76.5 in)	0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in), 0.127 mm (0.005 in)
Fortus 380mc CF™	35.6 x 30.5 x 30.5 cm (14 x 12 x 12 in)	92 cu in or 184 cu in	127 x 90.17 x 198.4 cm (50 x 35.5 x 76.5 in)	0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in), 0.127 mm (0.005 in)
Fortus 450mc™	40.6 x 35.6 x 40.6 cm (16 x 14 x 16 in)	92 cu in, 184 cu in, 500 cu in	127 x 90.17 x 198.4 cm (50 x 35.5 x 76.5 in)	0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in), 0.127 mm (0.005 in)
Stratasys F900™	91.4 x 60.7 x 91.4 cm (36 x 24 x 36 in)	92 cu in, 184 cu in, 500 cu in	277.2 x 168.3 x 202.7 cm (109.1 x 66.3 x 79.8 in)	0.508 mm (0.020 in), 0.330 mm (0.013 in), 0.254 mm (0.010 in), 0.178 mm (0.007 in), 0.127 mm (0.005 in)

Material Classification			
Material	Standard	Engineering	High Performance
ABS-M30™	●	○	○
ABS-M30j™	●	○	○
ABS-ESD7™	●	○	○
ASA	●	○	○
PLA	●	○	○
PC-ABS	○	●	○
PC	○	●	○
PC-ISO™	○	●	○
FDM™ Nylon 6	○	●	○
FDM™ Nylon 12	○	●	○
FDM™ TPU 92A	○	●	○
Antero™ 800NA	○	○	●
FDM™ Nylon 12 CF	○	○	●
ST-130™	○	○	●
ULTEM™ 9085 resin	○	○	●
ULTEM™ 9085 CG resin	○	○	●
ULTEM™ 1010 resin	○	○	●
ULTEM™ 1010 CG resin	○	○	●
PPSF	○	○	●

FDM Machine/Material Reference

Materials																			
Color	ABS-M30 ^{1,2}	ABS-M30i	ABS-ESD7	ASA ²	PLA	PC-ABS	PC ^{1,2}	PC-ISO	FDM Nylon 6	FDM Nylon 12	FDM TPU 92A	Antero 800NA	FDM Nylon 12CF	ST-130	ULTEM™ 9085 resin ¹	ULTEM™ 1010 resin	ULTEM™ 9085 CG resin	ULTEM™ 1010 CG resin	PPSF
Amber Translucent	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Black	●	○	●	●	●	●	○	○	●	●	●	○	●	○	●	○	○	○	○
Blue	●	○	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Blue Translucent	○	○	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Dark Blue	○	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Dark Gray	●	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Green	●	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Green Translucent	○	○	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Ivory	●	●	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Light Gray	○	○	○	●	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Medium Gray	○	○	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Natural	○	○	○	○	○	○	○	○	○	○	○	●	○	●	●	●	●	●	●
Natural Translucent	○	○	○	○	●	○	○	●	○	○	○	○	○	○	○	○	○	○	○
Nectarine	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Olive Green	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Orange	●	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Red	●	○	○	●	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Red Translucent	○	○	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
White	●	○	○	●	●	●	●	●	○	○	○	○	○	○	○	○	○	○	○
Yellow	●	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Yellow Translucent	○	○	○	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Support Material	(Soluble) SR-20™, SR-30 ² , SR-35, QSR™	(Soluble) SR-20, SR-30 ² , SR-35	(Soluble) SR-30 ² , SR-35	(Soluble) SR-30 ² , SR-35, QSR	(Breakaway), PLA	(Soluble) SR-20, SR-110™, QSR	(Soluble) SR-100™, (Breakaway) PC- Breakaway ²	(Breakaway) PC- Breakaway	(Soluble) SR-110	(Soluble) SR-110	(Soluble) QSR	(Breakaway) SUP9000B™	(Soluble) SR-110	(Breakaway) ST130_S™	(Breakaway) ULTEM™ 9085 resin Breakaway	(Breakaway) ULTEM™ 1010 resin Breakaway	(Breakaway) ULTEM™ 9085 resin Breakaway	(Breakaway) ULTEM™ 1010 resin Breakaway	(Breakaway) PPSF Breakaway

¹ Xtend 184 cu in canister

² Available in Xtend 500 cu in box

FDM Machine/Material Reference

Support Material

Material	Stratasys F120	Stratasys F170	Stratasys F270	Stratasys F370	Fortus 380mc	Fortus 380mc CF	Fortus 450mc	Stratasys F900
ABS-M30	SR30	QSR	QSR	QSR	SR30, SR35	-	SR30, SR35	SR30, SR35, SR20
ABS-M30i	-	-	-	-	SR30, SR35	-	SR30, SR35	SR30, SR35, SR20
ABS-ESD7	-	-	-	-	SR30, SR35	-	SR30, SR35	SR30, SR35
ASA	SR30	QSR	QSR	QSR	SR30, SR35	SR30, SR35	SR30, SR35	SR30, SR35
PLA	-	PLA	PLA	PLA	-	-	-	SR110
PC-ABS	-	-	-	QSR	SR110	-	SR110	SR110
PC	-	-	-	-	SR100, PCBASS*	-	SR100, PCBASS*	SR100, PCBASS*
PC-ISO	-	-	-	-	PCBASS*	-	PCBASS*	PCBASS*
FDM Nylon 6	-	-	-	-	-	-	-	SR110
FDM Nylon 12	-	-	-	-	SR110	-	SR110	SR110
FDM TPU 92A	-	QSR	QSR	QSR	-	-	-	-
Antero 800NA	-	-	-	-	-	-	SUP8000B	-
FDM Nylon 12CF	-	-	-	-	-	SR110	SR110	SR110
ST-130	-	-	-	-	-	-	ST130S	ST130S
ULTEM™ 9085 resin	-	-	-	-	-	-	BASS9085*	BASS9085*
ULTEM™ 1010 resin	-	-	-	-	-	-	BASS1010*	BASS1010*
ULTEM™ 9085 CG resin	-	-	-	-	-	-	BASS9085*	BASS9085*
ULTEM™ 1010 CG resin	-	-	-	-	-	-	BASS1010*	BASS1010*
PPSF	-	-	-	-	-	-	-	BASSPPSF*

* BASS stands for Breakaway Support System

HEADQUARTERS

7665 Commerce Way,
Eden Prairie, MN 55344
+1 800 801 6491 (US Toll Free)
+1 952 937-3000 (Intl)
+1 952 937-0070 (Fax)

1 Holtzman St., Science Park,
PO Box 2496
Rehovot 76124, Israel
+972 74 745 4000
+972 74 745 5000 (Fax)

STRATASYS.COM

ISO 9001:2008 Certified